

Single Row Tapered Roller Bearing

30200 Tapered Roller Bearing-30220J2

تعيين	30220J2
(الأبعاد الرئيسية (مم)	
د 1	100
د	180
ب	37
(KN) تصنيفات الحمل الأساسية	
DYC (كر)	246
stc (كور)	320
بو	36
(rpm) تقييمات السرعة	
تقييمات السرعة	2800
تحديد السرعة	3600
(الوزن (كجم	3.65
ISO335	
الأبعاد (ABMA)	3FB
الأبعاد ^٢ مم	
د	100
د 1 ^٢	133
ب	34
ج	29
r1 ² (دقيقة)	3
r3 ⁴ (دقيقة)	2.5
أ	35
أبعاد الدعامه والشرائح ^٢ مم	
(دا (كحد أقصى	116
(ديسبيل (دقيقة	112
(دا (دقيقة	157
(دا (حد أقصى	168
(ديسبيل (دقيقة	168
(كاليفورنيا (دقيقة	5
Cb (دقيقة)	8
ra (حد أقصى)	2.5
rb (حد أقصى)	2
قيمة	
هـ	0.43
ص	1.4
يو	0.8

GQZ high quality 30200 Single Row Tapered Roller Bearing

The dimensions of 30200 tapered roller bearing include an inner diameter of 10mm, an outer

diameter of 30mm and a height of 10.25mm.

The 30200 series tapered roller bearing are a commonly used mechanical part and are widely used in a variety of mechanical equipment. Their design features include separable parts, no seals, high speed usage characteristics, and the use of high carbon chrome bearing steel (GCr15) as the material. The rolling bodies of these bearings are tapered rollers with a convex raceway design and no sealing cap, making them suitable for general-purpose use, especially in applications requiring high-speed operation. In addition, the cages of 30200 series tapered roller bearings are made of stamped J steel plate and weigh about 0.036kg.

30200 tapered roller bearing are mainly subjected to radial mainly diameter, axial joint load, its load carrying capacity depends on the raceway angle of the outer ring, the larger the angle the greater the load carrying capacity. This kind of bearing belongs to the separated type, which means that the inner ring assembly (with roller and cage) can be mounted separately from the outer ring. According to the number of columns of rolling bodies in the bearing, it is divided into single row, double row and four rows of tapered roller bearings. For single row tapered roller bearings, the clearance needs to be adjusted by the user during installation, while for double row and four row tapered roller bearings, the clearance has been set according to the user's requirements at the time of shipment, and does not need to be adjusted by the user. Tapered roller bearings have conical inner ring and outer ring raceway, tapered rollers are arranged between the two, all the tapered surface of the projection line in the bearing axis of the same point of convergence. This design makes tapered roller bearings particularly suitable for bearing composite (radial and axial) loads, in which the axial load capacity is mostly determined by the contact angle α , the larger the α angle, the higher the axial load capacity. Therefore, tapered roller bearings play an important role in many applications due to their special design and excellent load carrying capacity.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gg@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com