

Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7004DT,7004DF,7004DB,7004C



تحميل الأرقام

صف	7004C
DB	7004DB
مدافع	7004DF
DT	7004DT

(الأبعاد الرئيسية (مم)

د	20
د	42
ب	12
(ص (دقيقة	0.6
r1 (دقيقة)	0.3

(N) تصنيفات الحمل الأساسية

سجل تجاري	11100
كو	6550

(kgf) تصنيفات الحمولة الأساسية

سجل تجاري	1130
كو	665

قيمة

فو	14
----	----

(تحديد السرعة (دورة في الدقيقة)

شح	26000
بترول	36000

(مسافة نقطة العمل (مم)

أ	10.1
---	------

أبعاد الدعامات والشرائح

(دا (دقيقة	25
(دا (حد أقصى	37
ra (حد أقصى)	0.6

الوزن

كلغ	0.076
-----	-------

(N) تصنيفات الحمل الأساسية (محمل مزدوج)

سجل تجاري	18000
كو	13100

(kgf) تصنيفات الحمل الأساسية (محمل مزدوج)

سجل تجاري	1840
كو	1330

(الحد من السرعة (محمل مزدوج) (دورة في الدقيقة)

شح	20000
بترول	30000

(a0) مسافة نقطة العمل (محمل مزدوج)

ترتيب ظهر إلى ظهر	20.3
الترتيب وجهاً لوجه	3.7

(أبعاد التثبيت (محمل مزدوج)

(ديسبيل (دقيقة	الأجزاء الميكانيكية المحدودة YouErJia شانغونغ
(ديسبيل (حد أقصى	39.5
rb (حد أقصى)	0.3

GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

Model:7000 series

Bore (Inner) Diameter: 10 mm

Outer Diameter: 26 mm

Width (Thickness): 16mm;

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

