

## Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7036DT,7036DF,7036DB,7036A 

## تحمل الأرقام

صف	<b>7036A</b>
DB	<b>7036DB</b>
مدافع	<b>7036DF</b>
DT	<b>7036DT</b>

## (الأبعاد الرئيسية (مم)

د	180
د	280
ب	46
(ص (دقيقة	2.1
r1 (دقيقة)	1.1

## (N) تصنيفات الحمل الأساسية

سجل تجاري	207000
كو	252000

## (kgf) تصنيفات الحمولة الأساسية

سجل تجاري	21100
كو	25700

## قيمة

فو	16.2
----	------

## (تحديد السرعة (دورة في الدقيقة

شحم	1900
بترول	2400

## (مسافة نقطة العمل (مم)

أ	89.4
---	------

## أبعاد الدعامة والشرائح

(دا (دقيقة	192
(دا (حد أقصى	268
ra (حد أقصى)	2

## الوزن

كلغ	10.5
-----	------

## (N) تصنيفات الحمل الأساسية (محمل مزدوج

سجل تجاري	335000
كو	505000

## (kgf) تصنيفات الحمل الأساسية (محمل مزدوج

سجل تجاري	34500
كو	51500

## (الحد من السرعة (محمل مزدوج) (دورة في الدقيقة

شحم	1500
بترول	2000

## (a0) (مسافة نقطة العمل (محمل مزدوج

ترتيب ظهر إلى ظهر	178.8
الترتيب وجهاً لوجه	86.8

## (أبعاد التثبيت (محمل مزدوج

(ديسيل (دقيقة	الأجزاء الميكانيكية المحدودة YouErJia شانونغ
(ديسيل (حد أقصى	273
rb (حد أقصى)	1

## GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

**Model:7000 series**

**Bore (Inner) Diameter: 10 mm**□

**Outer Diameter: 26 mm**□

**Width (Thickness): 16mm;**

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

